

# RH25 / SH40 Rainwater hoppers



Code	Outlet mm	Colour	A mm	B mm	C mm	D mm	E mm	Roof area m <sup>2</sup>	Flow rate litres/second	Weight kg
RH25PB	68	Black	405	192	254	150	440	360	7.56	1.2
RH25PAG	68	Anthracite grey	405	192	254	150	440	360	7.56	1.2
SH40PB	110	Black	405	192	254	150	440	720	15.12	1.2

Flow capacity based on a rainfall intensity of 0.021 litres/second per square metre of roof area

## Features

- Our largest rainwater hoppers offering an impressive flow rate up to 15.12 litres/second (based on 110mm outlet)
- Circular 68mm or 110mm outlet
- Stackable for easier transport and storage
- Outlet positioned at wall bracket distance, removing the need for a swan neck assembly
- External lugs can be easily removed for fixing in corners
- Drill start at the back of the hopper to help drill holes through the plastic if lugs are removed

## Material

PP (Polypropylene)

## Compatible fittings

RLE3 outlet adaptor - use with a pipe socket to convert circular 68mm outlet to fit square downpipe

## Standard

Meets performance and design requirements within BS EN 12056-3 Part 3: Roof drainage, Layout and Calculation

Issue date: Nov 2023